

Decoding

V77873_en

The **decoding** of a natural number n is a string of characters such that every two digits of n represent a character. For example, the decoding of $n = 6568$ is AD, because the ASCII code of the character A is 65 and the ASCII character of the character D is 68. Notice that n has two groups of two digits: 65 and 68. Another example: the decoding of 65666768 is ABCD, since n is composed of 65, 66, 67, and 68.

It is necessary to implement the **recursive** function `void decodificacio(int)` with the following specification:

PRE: The input is an integer n such that:

1. $n \geq 65$
2. $n = d_1d_2d_3d_4 \dots d_{m-1}d_m$.
3. m is even
4. for any pair of digits $d_i d_{i+1}$ (i odd) we have that $65 \leq d_i d_{i+1} \leq 90$.

POST: writes the decoding of n to the output channel `cout`.

Observation

Only recursive solutions are accepted.

IMPORTANT: You only need to submit the requested function, and possibly other necessary actions and functions. However, you must keep the type definitions and `#includes`.

Input

The input consists of a natural number $n \geq 65$ such that $n = d_1d_2d_3d_4 \dots d_{m-1}d_m$ m is even and for any pair of digits $d_i d_{i+1}$ such that i is odd, we have that $65 \leq d_i d_{i+1} \leq 90$.

Output

For each integer n , its decoding.

Sample input 1

```
65666768
6568
676665
88
```

Sample output 1

```
ABCD
AD
CBA
X
```

Problem information

Author: PRO1

Generation: 2026-01-25T13:11:54.829Z

© Jutge.org, 2006–2026.

<https://jutge.org>